



September 2008

## Floorsafe Stair Nosing Specifications

R-NS	10um anodised serrated aluminium 25mm x 48mm 3mm Thick – Weight 0.471kg/m
R-NR	10um anodised aluminium 30mm x 50mm 3mm thickness – Weight 0.412kg/m Inserts 42mm self adhesive rubber/cork 2.5mm thick
R-CB	10um anodised aluminium with bull nosed edge 25mm x 60mm Weight 0.680kg/m. Alloy Temper 6063/T5 Inserts 42mm self adhesive rubber/cork 2.5mm thick
R-CC	10um anodised aluminium 25mm x 63mm Weight 0.621kg/m. Alloy Temper 6063/T5 Inserts 42mm self adhesive rubber/cork 2.5mm thick
R-CF	10um anodised aluminium. 37mm x 71mm Weight 0.710kg/m. Alloy Temper 6063/T5 Inserts 51mm Rubber
R-KZ	10um Anodised Aluminium with bull nose edge 37mm x 80mm Weight 0.694kg/m. Alloy Temper 6063/T5
R-RN	Manufactured with 100% synthetic rubber(SBR) and the highest quality mineral aggregates, pigments and stabilizing agents. Thickness 5mm. 45mm x 60mm. Fire tested to ASTM E648 – FMVSS 302 – ASTM E662 – BSS-7293. Exceeds ADA requirements ASTM D2047 slip resistance.
R-NA	10um anodised aluminium. 37mm x 75mm Weight 0.770kg/m. Alloy Temper 6063/T5 Inserts 51mm rubber.
R-NAC	10um anodised aluminium. 37mm x 75mm Weight 0.815kg/m. Alloy Temper 6063/T5 Inserts 51mm rubber.
R-MN	1.6mm Galvanised metal angle coated with a 2-part polyurethane coating. The coating is of the highest quality, hard wearing & exceeds the recommendations of HB-197. This nosing also achieves a classification of V according to table 2 AS/NZS 4586:2004
R-NAL	Clear anodised to Class AA25. 25 micron thickness. Alloy 6060/T5. Weight 0.484 Kg/m. Luminous insert manufactured in Polypropylene which will resist cracking & chipping. This Profile exceeds slip resistance of pedestrian surfaces. AS 3661.1 - 1993

**FLOORSAFE SYDNEY**

**Ph: 1300 732 371 Fax: (02)9481-4516**

[info@floorsafesydney.com.au](mailto:info@floorsafesydney.com.au)

[www.floorsafesydney.com.au](http://www.floorsafesydney.com.au)